

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number  
WO 2004/003471 A2

(51) International Patent Classification<sup>7</sup>:

G01C

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number:

PCT/US2003/019941

(22) International Filing Date: 26 June 2003 (26.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/391,912 27 June 2002 (27.06.2002) US

(71) Applicant (for all designated States except US): THOMSON LICENSING S.A. [FR/FR]; 46, Quai A. Le Gallo, F-92648 Boulogne (FR).

(71) Applicant and

(72) Inventor: KENDALL, Scott, Allan [US/US]; 318 McIntosh Lane, Westfield, IN 46074 (US).

(74) Agents: TRIPOLI, Joseph, S. et al.; c/o Thomson Licensing Inc., Two Independence Way, Suite #200, Princeton, NJ 08540 (US).


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DISTANCE CHECK FOR TELEVISION SIGNAL RECEIVER HAVING AN EMERGENCY ALERT FUNCTION



WO 2004/003471 A2

(57) Abstract: A television signal receiver (20) having an emergency alert function is capable of checking a distance between a reference point and a point associated with a geographical area selected by a user during a setup process for the emergency alert function. According to an exemplary embodiment, the television signal receiver (20) includes a memory (27) operative to store data associated with the emergency alert function. A processor (27) is operative to receive an input representing a geographical area, and to enable a predetermined output responsive to the input using the data in the memory (27) when a distance between a reference point and a point associated with the geographical area exceeds a predetermined distance.